

Specifications

Wind-Free™ 1-Way Cassette

- 2-Step Cooling: Fast Cooling & Wind-Free™ Cooling.
- Blade angle between 37° and 87°, blade width 100 mm.
- Built-in humidity sensor.
- Height of only 135 mm.
- Built-in condensation drain pump (750 mmH₂O).



Indoor Unit			AJ026TNDKG/EU	AJ035TNDKG/EU
Capacity				
	Cooling	kW	2.6	3.5
	Heating @ +7 °C	kW	2.9	3.8
Performance				
Airflow Rate		m ³ /min	6.2/5.2/4.2	7.6/6.6/5.6
Sound Power	Cooling	dB(A)	50	55
Sound Pressure	H/M/L	dB(A)	32/29/26	37/33/30
Electrical Data				
Power Source	Φ, #, V, Hz		1Φ, 2, 220~240 V, 50 Hz	1Φ, 2, 220~240 V, 50 Hz
Power Consumption	Cooling	W	45	50
	Heating	W	45	50
Current Input	Cooling	A	0.23	0.25
	Heating	A	0.23	0.25
Dimensions				
Net Dimensions (W x H x D)		mm	970 x 135 x 410	970 x 135 x 410
Net Weight		kg	10.0	10.0
Refrigerant				
Piping Connections	Liquid Pipe	ø, inch	1/4	1/4
	Gas Pipe	ø, inch	3/8	3/8
Piping Connections	Drain Pipe	ø, mm	VP20 (OD 26, ID 20)	VP20 (OD 26, ID 20)
Others				
Panel	Model Code		PC11WFMAN	PC11WFMAN
	Net Dimensions (W x H x D)	mm	1,198 x 35 x 500	1,198 x 35 x 500
	Net Weight	kg	4.3	4.3
Accessories	Drain Pump		Included	Included
	Max. Lifting Height/ Displacement	mm / litres/h	750/24	750/24

Accessories




Wireless Remote Controller	Advanced Wired Controller	Simple Type Controller	Touch Controller	Wired Remote Controller	Wi-Fi Kit	Panel (Required)
AR-EH03E	MWR-WG00JN/ MWR-WG00KN	MWR-SH00N	MWR-SH11N	MWR-WE13N	MIM-H04EN	PC11WFMAN

Dimensional drawings

Wind-Free™ 1-Way Cassette

AJ026/035TNDKG/EU



NO	Name	Description
1	Gas pipe connection	ø12.70 (1/2)
2	Liquid pipe connection	ø6.35 (1/4)
3	Drain hose connection	VP20 (OD 26, ID 20)
4	Power supply/communication wiring conduits	
5	Air outlet louvre	
6	Air inlet grille	